


Value of Occupant Outreach:

Design and Evaluation of a Dorm Energy Efficiency Program


Dallase Scott BECC 2013




Problem Statement



Problem Statement



Dorm Energy Efficiency Project



Program Development

	Program Offerings	Experimental Dorms Morris & Champlin	Control Dorms Emery & Woolley
	 Building Upgrades: Installation of TRVs Building Automation Pipe & Valve Insulation Building Weatherization Upgrades to Lighting & Plumbing 		
	Email Communication	\checkmark	
Programing	Student to Student Outreach	\checkmark	
	Energy Showcase	\checkmark	
	Pledges	\checkmark	
	Posters	\checkmark	
	Smores Event	\checkmark	

Behavior & Outreach Programing



Fall

Winte

pring



Window Observations



Survey



Sub Metering



Service Response






Window Observations:

Control = Experimental =

- Eco Reps did on-site window observations
- Set time two days a week for four weeks.
- 50% Decrease in open windows with experimental group.






Survey Results:

Survey participants were asked:

How much do you agree with the following statements:

26 occupants responded to the survey **from each group**

Control Experimental



Brown Is:

"Committed to reducing 42% of its greenhouse gas emissions by 2020"






Survey Results:

Experimental group selfreported that they **open their windows less** when their heating is on. P=00.8

Survey participants were asked: How much do you agree with the following statements:



"I open the window when the heating is on."

1 Disagree Strongly

2 Disagree

3 Neutral


4 Agree

5 Agree Strongly



Sub Metering:

- Sub metering didn't start working until until February
- Difference with fallbacks between control group and experimental groups
- Operator adjusted setbacks





Sub Metering:


Table 1: A comparison of the commissioned and actual set points. Operator overrides are in red.

Set Point	Commissioned Value	Current Value				Description
Set Point		CHAMPLIN	MORRISS	EMERY	WOOLLEY	Description
OA- ENABLED- SP	55	60	55	55	55	Outdoor (OA) Temp at which heating is enabled
OALO-SP	0	40	30	0	0	OA Temp which drives HW supply temp to its highest setpoint
OAHI-SP	55	55	55	55	55	OA Temp which drives HW supply temp to its lowest setpoint
HWHI-SP	180	180	180	180	180	HW supply temp highest setpoint
HWLO-SP	120	140	120	120	120	HW supply temp lowest setpoint

Service Response:

Pembroke Quad Weekly Service Calls November 2012 - May 2013







Limitations

- Operator Setbacks
- Sub Metering
- Practitioners





Dallase Scott

Manager of Sustainability Services Dallase.S@GreenerU.com

